



DECLARATION OF PERFORMANCE No. 03-01-D/2022/EN

1. Unique identification code of the product type: Regulation Council of Europe no. 305/2011 Appendix IV listing 6: Chimneys, chimney flues.

Flexible acid-resistant chimney liner JAWAR DUOFLIX working in underpressure or overpressure

2. Type, batch or serial number: Diameter line of the product system JAWAR DUOFLIX

Diameter Dn [mm] 80	100	110	120	125	130	150	160	180	200	250	l
---------------------	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	---

3. Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer:

Chimney liners type **JAWAR DUOFLIX**—used as metal liners protecting brick chimneys against deterioration caused by gases and condensate from heating appliances run on gas, oil or wood working in underpressure with wet or dry gases.

4. Name, registered trade name or registered trade mark and contact address of the manufacturer:

Flexible chimney liners JAWAR DUOFLIX



JAWAR Spółka z o. o. 06-400 Ciechanów, ul. Sońska 89 06-450 Glinojeck, Zygmuntowo 1c

- 5. Name and contact address of the authorized representative: not applicable
- 6. System or systems of assessment and verification of constancy of performance of the construction product: **2**+
- 7. Name and identification number of the notified body, certificate of conformity of the factory production control:

Technický a zkušební ústav stavební Praha, s.p. (Technical and Test Institute for Construction Prague)

Notified Body 1020

Certificate number: 1020-CPR-030061488

8. Declared performance:

No	No Essential characteristics		PN-EN 1856-2:2009					
1.	Working temperature class	45	60°C	600°C				
2.	Material thickness	2 x 0,10						
3.	Distance to burnable materials	400 mm		500 mm				
4.	Pressure class	P1	N1	N1				
5.	Resistance to condensate	W						
6.	Resistance to corrosion	Vm						
7.	7. Type of material		50 (1.4404)					
8. Resistance to sootfire		G						
9.	Type of fuels		gas, oil, wood					
10.	Way of operation	overpressure underpressure		underpressure				
11.	11. Average chimney hight		15 mb					

- The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 8.
 This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.
- 10. First marking with the CE sign: 2007,-

Signed for and on behalf of the manufacturer by:

Ciechanów 21-07-2022 r.

Joonno
Petnomocnik ds. ZKP

Oxowhile

dr. Paweł Jarzyński Prezes Zarządu Jawar Sp. 9.0